

# Sun Chemical Rycoline®

## Main Edition™ 62 Plus Technical Data Sheet

Rycoline Main Edition 62 Plus is designed to provide enhanced performance at low dosages. The unique wetting technology and ultra mild acid formula helps to provide water reductions on press, color enhancements and reductions in piling.

### typical characteristics and features

Rycoline Main Edition 62 Plus is formulated to have the following properties:

- Enhanced piling control
- Ultra mild acid
- Concentrated formula

### technical information and ink handling

#### Physical properties

- Conductivity: 600 mmho's per ounce (768 mmho's per one percent (1%))
- VOC's: Zero (0)
- pH: 4.8 - 6.2 properly diluted

#### Applications

#### directions

Mix 1.5% - 2% (2 - 2.5 ounces per gallon) of Main Edition 62 Plus in water for desired results.

#### application equipment

Rycoline Main Edition 62 Plus is designed to run on all cold set dampening systems except turbo brush.

#### ink suitability

Main Edition 62 Plus is designed for use with all non-FOGRA cold set ink applications.

Product Selection	EMG Number	SAP Number 5-Gallon Pail	SAP Number 55-Gallon Drum	SAP Number 275-Gallon Tote
Main Edition 62 Plus	265581	90959703	90921366	90921367

#### clean - up

See SDS for clean up of spills and personal precautions.

#### storage consideration

Do not freeze. When stored in the original unopened container, Main Edition 62 Plus has a one (1) year shelf-life from date of manufacture.

#### safety, health and environment

Main Edition 62 Plus is to be used in accordance with normal standards of industrial hygiene and good manufacturing practice. Please refer to the supplied Safety Data Sheet for specific information.

Printing inks, coatings and printing residues should be disposed of in accordance with local and national regulations.

This information has been compiled from experience gained in field conditions and detailed laboratory testing. However, the product's performance and its suitability for the customer's purpose depend on the particular conditions of use and the material being printed. We recommend that customers satisfy themselves that each product meets their requirements in all respects before commencing a print run. Since we cannot anticipate or control the conditions under which our products are used it is not possible to guarantee their performance.

All sales are subject to our standard terms and conditions for sale. The information contained in this technical data sheet is only a recommendation and may need to be altered to suit the conditions and efficiency of the equipment employed. Our products are not designed for use in conjunction with those of any other ink maker or similar supplier unless agreed to in writing.

